



### Chain Wrench

A double jaw gives fast, ratchet-like action in either direction. The heavy-duty model has replaceable alloy steel jaws. The light-duty model has a one-piece forged alloy steel handle and jaw. Ideal for use in close quarters.

Catalog No.	Model No.	Description	Rated Pipe Capacity		Actual O.D. Capacity		Chain Length		Weight		Std. Pack
			in.	mm	in.	mm	in.	mm	lb.	kg	
31310	C-12	Light-Duty Chain Wrench	2	50	4	100	15 <sup>3</sup> / <sub>4</sub>	390	1 <sup>3</sup> / <sub>4</sub>	0,8	1
31315	C-14	Heavy-Duty Chain Wrench	2	50	5	125	18 <sup>1</sup> / <sub>2</sub>	460	2 <sup>3</sup> / <sub>4</sub>	1,2	1
31320	C-18	Heavy-Duty Chain Wrench	2 <sup>1</sup> / <sub>2</sub>	60	5	125	20 <sup>1</sup> / <sub>4</sub>	500	6	2,7	1
31325	C-24	Heavy-Duty Chain Wrench	3	75	5	125	20 <sup>1</sup> / <sub>4</sub>	500	8 <sup>1</sup> / <sub>4</sub>	3,7	1
31330	C-36	Heavy-Duty Chain Wrench	4 <sup>1</sup> / <sub>2</sub>	110	7 <sup>1</sup> / <sub>2</sub>	185	29	725	15 <sup>3</sup> / <sub>4</sub>	7,1	1



### Strap Wrench

Best for any polished pipe. Strong, woven nylon strap gives tight grip. Two models available for plastic pipe. Polyurethane-coated strap prevents scratching. Replaceable straps available.

Catalog No.	Model No.	Handle Length		Strap Length		Strap Width		Pipe Capacity		Tube Capacity (O.D.)		Weight		Std. Pack
		in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lb.	kg	
31335	1	11 <sup>3</sup> / <sub>4</sub>	300	17	425	1/2	12	2	50	3 <sup>1</sup> / <sub>2</sub>	90	1 <sup>1</sup> / <sub>4</sub>	0,5	1
31340	2	11 <sup>3</sup> / <sub>4</sub>	300	17	425	1 <sup>1</sup> / <sub>8</sub>	30	2	50	3 <sup>1</sup> / <sub>2</sub>	90	1 <sup>3</sup> / <sub>4</sub>	0,8	1
31345	2	11 <sup>3</sup> / <sub>4</sub>	300	30	760	1 <sup>1</sup> / <sub>8</sub>	30	2	50	5 <sup>1</sup> / <sub>2</sub>	135	1 <sup>3</sup> / <sub>4</sub>	0,8	1
31350	2	11 <sup>3</sup> / <sub>4</sub>	300	24	600	1 <sup>1</sup> / <sub>8</sub>	30	2	50	5 <sup>1</sup> / <sub>2</sub>	135	1 <sup>3</sup> / <sub>4</sub>	0,8	1
31355	2P*	11 <sup>3</sup> / <sub>4</sub>	300	17	425	1 <sup>1</sup> / <sub>16</sub>	27	2	50	3 <sup>1</sup> / <sub>2</sub>	90	1 <sup>3</sup> / <sub>4</sub>	0,8	1
31360	5	18	450	29 <sup>1</sup> / <sub>4</sub>	750	1 <sup>3</sup> / <sub>4</sub>	45	5	125	7	175	2	0,9	1
31365	5	18	450	48	1200	1 <sup>3</sup> / <sub>4</sub>	45	5	125	12	300	2	0,9	1
31370	5P*	18	450	29 <sup>1</sup> / <sub>4</sub>	750	1 <sup>3</sup> / <sub>4</sub>	45	5	125	5 <sup>1</sup> / <sub>2</sub>	135	2 <sup>1</sup> / <sub>8</sub>	1,0	1

\*Strap designed for use with plastic pipe.



### Chain Tongs

Designed and sized to provide extra leverage for the toughest jobs. All models feature double-end jaw styles which can be reversed, except Model 3215 which is a single-end tong.

Catalog No.	Model No.	Description	Total Length		Pipe Capacity		Chain Length		Chain Breaking Strain*		Weight		Std. Pack
			in.	mm	in.	mm	in.	mm	lb.	kg	lb.	kg	
92660	3215	Single-End	87	2209	4-18	114-457	74 <sup>1</sup> / <sub>2</sub>	1892	56,000	25,401	139	62	1
92665	3229	Double-End	27	686	1/4-2 <sup>1</sup> / <sub>2</sub>	13-73	17 <sup>1</sup> / <sub>2</sub>	445	13,800	6,260	9	5	1
92670	3231	Double-End	37	939	3/4-4	26-114	22 <sup>1</sup> / <sub>2</sub>	572	17,600	7,983	17	8	1
92675	3233	Double-End	44	1117	1-6	33-168	32	813	20,100	9,117	24	11	1
92680	3235	Double-End	50	1270	1 <sup>1</sup> / <sub>2</sub> -8	48-219	40 <sup>1</sup> / <sub>2</sub>	1029	22,000	9,979	32	15	1
92685	3237	Double-End	64	1625	2-12	60-323	55 <sup>1</sup> / <sub>2</sub>	1410	31,000	14,061	56	25	1

\*All chains are tested to 2/3 of their breaking strength.